Technical Specifications

exacqVision EL-Series "Mini" IP Camera Server

exacq/isionEL mini

(intel) Atom[®]_{inside}

MODEL NUMBER: MAXIMUM HD STORAGE:

MAXIMUM HARD DRIVES:



•



Low Power Consumption, Cost Efficient Small Form Factor IP Camera Servers Factory Installed exacqVision Software

IPS-0500-ELM

500 GB

1



Compatible Client Operating Systems: Windows 7, Windows Vista, Windows XP, Windows Server 2003/2008 (32-bit or 64-bit) Ubuntu Linux & Mac OS X





11955 Exit Five Parkway, Building 3 • Fishers, IN, 46037, USA • +1.317.845.5710 • www.exacq.com

exacqVision^{EL-Series}

Common Specs - All EL-Mini Servers

-	
POWE	R: Universal power supply
INPUT VOLTAG	E: 120/240 VAC auto-sensing
POWER CONSUMPTIO	N: 35 watts max
OPERATING TEMPERATUR	E: 40° – 95°F (4.5° – 35°C)
RELATIVE HUMIDIT	Y: 5-95% RH (non-condensing)
MEMOR	Y: 1 GB RAM
PROCESSO	R: Intel Atom Dual Core
N	C: Gigabit 1000Base-T RJ-45
THROUGHPU	T: 18 MB/second sustained
USB2 PORT	S: 6 (2 front / 4 rear)
VIDEO OUTPU	T: 1 VGA (DB-15)
IP RECORDING RESOLUTIO	N: Up to 10 Megapixel, camera dependent
IP COMPRESSIO	N: H.264, M-JPEG or MPEG-4 (camera dependent)
IP CAMERA CHANNEL	S: Up to 24 per server
IP CAMERA FRAME RAT	E: Camera dependent
SERIAL CONNECTION	S: RS-232
SERVER OPERATING SYSTE	A: Ubuntu Linux on Internal Flash Drive
WARRANT	V: 2 years parts & Jahor
REGULATOR	
MIS	C: Watchdog Timer, Keyboard, Mouse, DVD/CD RW